

HOME OFFICE

PO Box 1605 5409 Hamlet Drive Findlay, Ohio 45840-1605 USA inquiries@rowmark.com

TECHNICAL SUPPORT

877.769.6275 /// 419.425.8974 techhelp@rowmark.com

EUROPE OFFICE/WAREHOUSE

Schaarbeekstraat 44 9120 Beveren-Waas Belgium +32 (0)3 870 41 10 emea@rowmark.com

CUSTOM REQUESTS

800.243.3339 /// 419.425.2407 customerservice@rowmark.com

877.rowmark rowmark.com



Engage. Interact. Share.









#Rowmark

Flexible, lightweight & tough...

This product line combines the classic crisp definition of real brass with all the advantages of thin, flexible acrylic.

- /// Available with or without adhesive.
- /// To order with adhesive, add a "9" to the end of the six digit code.





























FLEXIBRASS® & FLEXICOLOR®



602-677 2-ply .020"



602-672 2-ply .020"



602-937 2-ply .020"



602-577 2-ply .020"



602-572 2-ply .020"




602-363 2-ply .020"



602-362 2-ply .020"



602-735 2-ply .020"



602-894 2-ply .020"



602-874 2-ply .020"



602-884 2-ply .020"



602-684 2-ply .020"



602-734 2-ply .020"



602-754 2-ply .020"



602-794 2-ply .020"



602-714 2-ply .020"



602-744 2-ply .020"



602-602 2-ply .020"



602-512 2-ply .020"



602-204 2-ply .020"



602-402 2-ply .020"



602-417 2-ply .020"



602-427 2-ply .020"



602-413 2-ply .020"



602-423 2-ply .020"



602-354 2-ply .020"



602-334 2-ply .020"



602-344 2-ply .020"



602-394 2-ply .020"





602-652 2-ply .020"

Brushed Blue/ Brass

602-557 2-ply .020"



602-552 2-ply .020"



602-457 2-ply .020"



602-452 2-ply .020"

TECHNICAL SPECIFICATIONS

Material

Microsurfaced impact acrylic

Finish

Matte non-glare Brushed metal Patterned Gloss

Sheet Size

24-1/8" x 48-3/4" // 613mm x 1238mm Port Wine & Harbor Grey**: 23-1/2"x 49" // 597mm x 1245mm

Engraving Depth

.003" // 0.08mm

Usage Interior Signage Trophies, Awards & Plaques

Capabilities

Bevels Bonds Drills Heat Bendable Hot Stamps Laser Vector Cuts Screen Prints Saws Shears (works on thicknesses 1/16" & under) Permits Fine Detail Engraving

♦ Not recommended for harsh or high humidity indoor or outdoor applications.

Available with or without adhesive. To order with adhesive, add an "9" to the end of the six digit code.