



HOME OFFICE

PO Box 1605
5409 Hamlet Drive
Findlay, Ohio 45840-1605 USA
inquiries@rowmark.com

EUROPE OFFICE/WAREHOUSE

Schaarbeekstraat 44
9120 Beveren-Waas
Belgium
+32 (0)3 870 41 10
emea@rowmark.com

TECHNICAL SUPPORT

877.769.6275 /// 419.425.8974
techhelp@rowmark.com

CUSTOM REQUESTS

800.243.3339 /// 419.425.2407
customerservice@rowmark.com

877.rowmark / rowmark.com



Engage. Interact. Share.



Impress with Reverse LaserMark®

Specially designed for the laser engraver, this line has a clear, non-glare matte finish over a layer of rich color. It offers a crisp, clean image and ultra-fine laser lettering, with a durable surface that resists fingerprints.

Achieve special effects with reverse engraving and backpainting. Reverse LaserMark® will help you make your best impression.



REVERSE LASERMARK®



Matte/Red	Matte/Burgundy	Matte/Ribbon Pink	Matte/Yellow	Matte/Bright Green	Matte/Blue	Matte/Navy Blue	Matte/White	Matte/Ivory	Matte/Dark Brown
922-601 2-ply 1/16"	922-621 2-ply 1/16"	922-661 2-ply 1/16"	922-701 2-ply 1/16"	922-931 2-ply 1/16"	922-511 2-ply 1/16"	922-551 2-ply 1/16"	922-201 2-ply 1/16"	922-221 2-ply 1/16"	922-841 2-ply 1/16"
Matte/Black	Matte/Smooth Gold*	Gloss/Smooth Gold*	Matte/Smooth Silver*	Gloss/Smooth Silver*	Matte/Clear	Clear/Clear			
922-401 2-ply 1/16"	922-711 2-ply 1/16" 942-711 2-ply 1/8"	922-710 2-ply 1/16" 942-710 2-ply 1/8"	922-341 2-ply 1/16" 942-341 2-ply 1/8"	922-340 2-ply 1/16" 942-340 2-ply 1/8"	311-101 1-ply 1/32" 322-101 1-ply 1/16" 342-101 1-ply 1/8"	411-100 1-ply 1/32" 422-100 1-ply 1/16" 442-100 1-ply 1/8"			

REVERSE LASERMARK® TECHNICAL SPECIFICATIONS

Material

Microsurfaced impact acrylic for reverse engraving

Finish

Matte non-glare
Gloss ■

Sheet Size

24-1/8" x 48-3/4" //
613mm x 1238mm

Engraving Depth

.003" // 0.08mm

Usage

ADA Compliant/Tactile Signage
Exterior Signage
Interior Signage
Illuminated Wayfinding
Personal Identification

Capabilities

Back-lighting Bevels
Bonds Drills
Heat Bendable Hot Stamps
Saws Screen Prints
Laser Vector Cuts
Shears (*works on thicknesses 1/16" & under*)
Permits Fine Detail Engraving

*Some LaserMark® Reverse foils are not recommended for applications in which UV stability is a requirement.

