



HOME OFFICE

PO Box 1605
5409 Hamlet Drive
Findlay, Ohio 45840-1605 USA
inquiries@rowmark.com

EUROPE OFFICE/WAREHOUSE

Schaarbeekstraat 44
9120 Beveren-Waas
Belgium
+32 (0)3 870 41 10
emea@rowmark.com

TECHNICAL SUPPORT

877.769.6275 /// 419.425.8974
techhelp@rowmark.com

CUSTOM REQUESTS

800.243.3339 /// 419.425.2407
customerservice@rowmark.com

877.rowmark / rowmark.com



Engage. Interact. Share.



Keep safety first with the Safe-T-Mark line.

Rowmark's **Safe-T-Mark**, a fabrication-friendly alternative to traditional phenolic materials, compares to Norplex, Lamacoid and Melamine in flame tests and electrical conductivity, making it the ideal choice for industrial tags, equipment identification tags, electrical tags and control panels.

Avoid the handling and fabrication frustration of traditional phenolic sheet materials. Choose this improved FR material that fabricates with ease!



Safe-T-Mark

SAFE-T-MARK



Red/ White	Vibrant Orange/Black	Yellow/ Black	Bright Green/ White	Blue/ White	White/ Black	Grey/ White	Grey/ Black	Black/ White
FR222-6022-ply 1/16" FR223-6023-ply 1/16"	FR222-6242-ply 1/16" FR223-6243-ply 1/16"	FR222-7442-ply 1/16" FR223-7443-ply 1/16"	FR222-9322-ply 1/16" FR223-9323-ply 1/16"	FR222-5122-ply 1/16" FR223-5123-ply 1/16"	FR222-2042-ply 1/16" FR223-2043-ply 1/16"	FR222-3122-ply 1/16" FR223-3123-ply 1/16"	FR222-3142-ply 1/16" FR223-3143-ply 1/16"	FR222-4022-ply 1/16" FR223-4023-ply 1/16"

TECHNICAL SPECIFICATIONS

Fabrication friendly alternative to traditional phenolic materials for indoor applications. Electrically non-conductive, insulative, fire retardant, non-flammable.

Material
Fire retardant functional polymer

Finish
Matte non-glare

UL94-V0 fire-rating

Sheet Size
24-1/8" x 48-3/4" //
613mm x 1238mm

Engraving Depth
.003" // 0.08mm

Usage
Control Panels
Equipment ID Tags
Fire Retardant
Industrial Signage/Tags
Safety Signage

Capabilities
Bevels
Drills
Hot Stamps
Screen Prints
Shears (works on thicknesses 1/16" & under)

Bonds
Heat Bendable
Saws
Permits Fine Detail Engraving

