

Specifications

Material

» Microsurfaced impact acrylic

Sheet Size

» 24 1/8" x 48 3/4" (613 x 1238mm)

Finish

- » Matte non-glare
- » Satin grain
- » Gloss■

Thickness 2-ply

- » .010" (.25mm) Use UG662 as first digits in item code.
- » .020" (.5mm) Use UG602 as first digits in item code.
- » .1/16" (1.6mm) Use UG922 as first digits in item code. (Gauges are approximate.)

Engraving Method

- » Laser
- » Rotating carbide

Engraving Depth

» .005" (.13mm)

Usage

- » Interior Signage
- » Exterior Signage
- » Personal Identification
- » Control Panels
- » Equipment ID Tags
- » Safety Signage
- » Recreational Signage
- » Industrial Signage/Tags
- » Trophies, Awards, & Plaques

Fabrication

- » Saws
- » Drills
- » Shears
- » Laser Vector Cuts
- » Bevels
- » Heat Bendable
- » Screen Prints
- » Hot Stamps
- » Bonds
- » Permits Fine Engraving

Visit www.rowmark.com for Rowmark's complete line of products for rotary engraving, laser engraving and sublimation.

Find answers to all your questions in the Technical Help section. Be sure to check out support tools under the Sales Tools and Downloads sections.

7/21

To request a sample or promotional literature, please call 1-877-ROWMARK (419-429-3160) or email samples@rowmark.com. For technical assistance, call 1-877-ROWMARK (419-429-3160), visit www.rowmark.com or email inquiries@rowmark.com.

Can't find exactly what you're looking for? We can build any combination of cap and core within the UltraGrave® product line. Contact your authorized Rowmark distributor or speak with one of our customer service specialists at 1-800-243-3339 (419-425-2407).



UltraGrave® Sign Kit

Fabricate the UltraGrave® Sign Kit by downloading the file found under the downloads section of our website at www.rowmark.com.















